

## FirePro® Condensed Aerosol generators: Technical information summary

Model	Weight (g)		Dimension (mm)			Activation mode <sup>(1)</sup>	Distance from generator's outlet at T <sub>N</sub> temperature (m)		Aerosol discharge time (s)		Stream length - (m)	Number of discharge outlet		
	Gross	Net	Height	Diameter			Electrical	T <sub>1</sub>	T <sub>2</sub>	Min		Max	1	2
				Height	Width									
FP-100S	1370	100	155	84		✓	0	0.15	5	10	1.0	✓		
FP-200S	1840	200	185	84		✓	0.3	0.55	5	10	2.0	✓		
FP-500S	3340	500	260	84		✓	0.4	0.8	5	10	2.0	✓		
FP-1200	10900	1200	167	216	300	✓	0.25	1.65	15	20	3.5	✓		
FP-2000	15500	2000	185	300	300	✓	0.5	1.4	15	20	3.5	✓		
FP-3000	16300	3000	185	300	300	✓	1.0	2.2	15	20	3.5	✓		
FP-5700	26400	5700	300	300	300	✓	0.85	2.2	15	20	5.0	✓		

### Note and Legend

Symbol	Description
T <sub>1</sub>	Aerosol stream temperature from generator discharge outlet equal or less than 200° C
T <sub>2</sub>	Aerosol stream temperature from generator discharge outlet equal or less than 75° C
(1)	In case of generator's system activation failure the <b>SBK</b> (solid compound) <b>FirePro®</b> will start by himself the aerosol forming reaction reaching the temperature of 300° C.
	-

Manufactured by

**FirePro Systems Ltd.**

Master dealers / Distributor

Trade Mark

**FirePro®**